Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-284-6907

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.406 inches |
| Tempurature Rating: |
| -55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.766 inches |
| Minimum Inside Bending Radius: |
| 1.750 inches |
| Exterior Color: |
| Blue |
| End Application: |
| 2320-01-123-1602 |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Reusable end fittings |
| Burst Test Pressure: |
| 5000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided polyester cord and 2nd layer braided wire and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 1250.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 1st end |
| Seat Angle: |
| 45.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 2500.0 pounds per square inch |
| Vacuum In Torr: |
| 50.8 |
| Inside Surface Condition: |
| Smooth |
| |

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:

38.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon and ethylene glycol and air single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0