NSN 4720-01-284-7422

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-284-7422

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.125 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
1.500 inches
Minimum Inside Bending Radius:
9.000 inches
End Application:
3810-01-205-2716
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
2500.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:
625.0 pounds per square inch
Thread Size:
1.688 inches 1st end
Hydrostatic Test Pressure:
1250.0 pounds per square inch
Vacuum In Torr:
254.0
Inside Surface Condition:
Smooth
Measuring Method And Length:
108.000 inches
Media For Which Designed:

Air and fuel/oil, hydrocarbon single response

NSN 4720-01-284-7422

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Un 1st end
Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0