

View Online at <https://aerobasegroup.com/nsn/4720-01-285-2878>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.750 inches

Temperature Rating:

-100.0 degrees fahrenheit single response and 350.0 degrees fahrenheit single response

Outside Diameter:

0.891 inches

Minimum Inside Bending Radius:

9.000 inches

End Application:

3805-01-2605163, scoop-loader

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

4000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

1.062 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Heat resistant and vibration resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

1574.0 millimeters

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0