NSN 4720-01-285-9614



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-285-9614 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.380 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response **Outside Diameter:** 0.620 inches Angle Between Rigid Elbow Fittings In Deg: 90.0 **End Application:** Martin marietta aerospace, orlando division; lantern target pod **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Elbow 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 300.0 pounds per square inch **Layer Composition And Location:** 1st layer braided polyamide cord and outer layer braided polyester cord **Maximum Operating Pressure:** 150.0 pounds per square inch **Thread Size:** 0.875 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 600.0 pounds per square inch Flow Angle: 90.0 degrees 1st end **Inside Surface Condition:**

Smooth **Measuring Method And Length:**

9.400 inches working

NSN 4720-01-285-9614

Nonmetallic Hose Assembly - Page 2 of 2



_		•	_	
ı	hread	Series	1)66	ignator:
•	mcaa	OCI ICS	D C3	igilatoi.

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0