NSN 4720-01-286-0232

Cross Sectional Shape:

Round

Metallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-286-0232

Round
Inside Diameter:
3.070 inches
Tempurature Rating:
100.0 degrees fahrenheit single response
Bolt Circle Diameter:
6.000 inches 1st end
Flange Thickness:
0.940 inches 1st end
Inner Conveying Tube Style:
Annular close-pitch corrugated
Bolt Hole Quantity:
4 1st end
Flange Outside Diameter:
7.500 inches 1st end
Connection Style:
Raised 1st end
Bolt Hole Diameter:
0.750 inches 1st end
Raised Face Diameter:
4.250 inches 1st end
End Flange Construction:
End Flange Construction: Solid 1st end
-
Solid 1st end
Solid 1st end End Connection Design:
Solid 1st end End Connection Design: Straight 1st end
Solid 1st end End Connection Design: Straight 1st end Connection Type:
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided:
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Identical ends
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Identical ends Layer Composition And Location:
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided corrosion resistant steel wire
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 190.0 pounds per square inch
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 190.0 pounds per square inch Hydrostatic Test Pressure:
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 190.0 pounds per square inch Hydrostatic Test Pressure: 380.0 pounds per square inch
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 190.0 pounds per square inch Hydrostatic Test Pressure: 380.0 pounds per square inch Measuring Method And Length:
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 190.0 pounds per square inch Hydrostatic Test Pressure: 380.0 pounds per square inch Measuring Method And Length: 24.000 inches
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 190.0 pounds per square inch Hydrostatic Test Pressure: 380.0 pounds per square inch Measuring Method And Length: 24.000 inches Flange Style:
Solid 1st end End Connection Design: Straight 1st end Connection Type: Raised face flange 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 190.0 pounds per square inch Hydrostatic Test Pressure: 380.0 pounds per square inch Measuring Method And Length: 24.000 inches Flange Style: Round w/ bolt holes 1st end

NSN 4720-01-286-0232

Metallic Hose Assembly - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A542a0