

View Online at <https://aerobasegroup.com/nsn/4720-01-286-3212>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.920 inches

Minimum Inside Bending Radius:

4.000 inches

Exterior Color:

Black

End Application:

3895-01-207-6347, kettle, mdl tps-165-a

Connection Style:

Swivel, plain 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external pipe 1st end

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

1st layer braided polyamide cord and 2nd layer braided polyamide cord and outer layer molded rubber, ethylene propylene

Maximum Operating Pressure:

1250.0 pounds per square inch

Thread Size:

0.500 inches 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

48.000 inches

Special Features:

One fixed and one swival fitting

Thread Series Designator:

Nptf 1st end

Specification Data:

81343-j1402 professional/industrial association standard

Specification Or Standard:

A1 table

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0