Nonmetallic Hose Assembly - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/4720-01-286-3213

Cros	ss Sectional Shape:
Rou	nd
Thre	ead Class:
3b 1	st end
Thre	ead Direction:
Righ	t-hand 1st end
Insid	de Diameter:
0.40	6 inches
Tem	purature Rating:
-65.0	0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outs	side Diameter:
0.56	2 inches
Mini	mum Inside Bending Radius:
4.62	5 inches
Con	nection Style:
Swiv	el nut flare 2nd end
End	Connection Design:
Strai	ight 1st end
Con	nection Type:
Thre	aded internal tube 1st end
Burs	st Test Pressure:
8000	0.0 pounds per square inch
Laye	er Composition And Location:
Oute	er layer braided corrosion resistant steel wire
Max	imum Operating Pressure:
1500	0.0 pounds per square inch
Thre	ead Size:
0.75	0 inches 2nd end
Seat	t Angle:
37.0	degrees 2nd end
Hyd	rostatic Test Pressure:
3000	0.0 pounds per square inch
Flow	v Angle:
90.0	degrees 2nd end
Insid	de Surface Condition:
Smo	poth
Mea	suring Method And Length:
23.0	00 inches
Thre	ead Series Designator:
Unf 2	2nd end
She	If Life:
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0