

View Online at <https://aerobasegroup.com/nsn/4720-01-286-6410>

Cross Sectional Shape:

Round

Inside Diameter:

2.020 inches

Temperature Rating:

-54.0 degrees celsius and 121.0 degrees celsius single response

Flange Thickness:

0.358 inches 2nd end

Outside Diameter:

2.940 inches

Minimum Inside Bending Radius:

12.500 inches

Exterior Color:

Black

Center To Center Distance Between Bolt Holes Along Width:

2.375 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

2.375 inches 1st end

Bolt Hole Quantity:

4 2nd end

Flange Length:

3.000 inches 2nd end

Flange Width:

3.000 inches 2nd end

Connection Style:

Raised swivel w/ gasket groove 2nd end

Bolt Hole Diameter:

0.328 inches 2nd end

Raised Face Height:

0.077 inches 2nd end

Raised Face Diameter:

2.760 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Raised face flange 2nd end

Layer Composition And Location:

1st layer spirally laid brass wire and outer layer spirally laid brass wire

Maximum Operating Pressure:

100.0 pounds per square inch

Hydrostatic Test Pressure:

300.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

64.350 inches and 65.650 inches

Flange Style:

Rectangular (includes square) 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A542a0