

View Online at <https://aerobasegroup.com/nsn/4720-01-286-8609>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

1.250 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Flange Thickness:**

0.495 inches 2nd end

**Outside Diameter:**

1.870 inches

**Minimum Inside Bending Radius:**

16.500 inches

**Flange Outside Diameter:**

2.000 inches 2nd end

**Connection Style:**

Plain swivel 2nd end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Plain face flange 2nd end

**Burst Test Pressure:**

4500.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

1125.0 pounds per square inch

**Hydrostatic Test Pressure:**

2250.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Abrasion resistant and oil resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

20.000 inches

**Flange Style:**

Round w/ out bolt holes 2nd end

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0