NSN 4720-01-286-8612

Nonmetallic Hose Assembly - Page 1 of 2



view Online at https://aerobasegroup.com/hsn/4720-01-266-6612
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
1.953 inches
Minimum Inside Bending Radius:
5.500 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Self-sealing
Burst Test Pressure:
600.0 pounds per square inch
Layer Composition And Location:
1st layer braided polyester cord and outer layer braided polyester cord
Maximum Operating Pressure:
100.0 pounds per square inch
Thread Size:
1.312 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
300.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:

25.000 inches

Thread Series Designator:

Unf 2nd end

NSN 4720-01-286-8612

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0