NSN 4720-01-287-2472

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-287-2472

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.485 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.905 inches
Minimum Inside Bending Radius:
6.500 inches
Hose Or Tubing Specification/std Data:
Sae as604, size 10-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Second End Relationship With First End:
Identical
Burst Test Pressure:
12000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire err-100
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.875 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:

Smooth

6000.0 pounds per square inch
Inside Surface Condition:

NSN 4720-01-287-2472

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 37.500 inches Special Features: Inner conveying tube material-plastic, tetrafluoroethylene Thread Series Designator: Unjf 1st end Specification Data: 81343-as621 professional/industrial association standard Shelf Life: N/a Unit Of Measure: --Demilitarization: No

Fiig: A542a0