

View Online at <https://aerobasegroup.com/nsn/4720-01-287-2473>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.485 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

**Outside Diameter:**

0.905 inches

**Minimum Inside Bending Radius:**

6.500 inches

**Hose Or Tubing Specification/std Data:**

Sae as604, size 10-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Connection Style:**

Swivel nut, flareless 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting stainless steel all ends

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

12000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire err-100

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

0.875 inches 1st end

**Seat Angle:**

12.0 degrees 1st end

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

40.750 inches

**Special Features:**

Inner conveying tube material-plastic, tetrafluoroethylene

**Thread Series Designator:**

Unjf 1st end

**Specification Data:**

81343-as621 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0