

View Online at <https://aerobasegroup.com/nsn/4720-01-287-7811>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.852 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outside Diameter:

1.380 inches

Minimum Inside Bending Radius:

9.625 inches

Hose Or Tubing Specification/std Data:

Sae as604 size 16-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel nut, flareless 2nd end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Thready Qty Per Inch (tpi):

12 2nd end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

12000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire err-100

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

1.312 inches 2nd end

Seat Angle:

12.0 degrees 2nd end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

16.250 inches

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-plastic, tetrafluoroethylene

Thread Series Designator:

Unj 2nd end

Specification Data:

81343-as623 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0