## NSN 4720-01-287-8883

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-287-8883

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.602 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
1.060 inches
Minimum Inside Bending Radius:
7.750 inches
Hose Or Tubing Specification/std Data:
Sae as604, size 12-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
12000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire err-100
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:

\_

12.0 degrees 1st end

## NSN 4720-01-287-8883

Nonmetallic Hose Assembly - Page 2 of 2



Hydrostatic Test Pressure:
6000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
28.250 inches
Special Features:
Inner conveying tube material-plastic, tetrafluoroethylene
Thread Series Designator:
Unj 1st end
Specification Data:
81343-as621 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0