NSN 4720-01-288-1942

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-288-1942

Right-hand 1st end			
Inside Diameter:			
0.602 inches			
Tempurature Rating:			
-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response			
Outside Diameter:			
0.884 inches			
Minimum Inside Bending Radius:			
3.880 inches			
End Application:			
1190-01-195-0904			
Connection Style:			
Swivel nut flare 2nd end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Thready Qty Per Inch (tpi):			
12 2nd end			
Burst Test Pressure:			
12000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer braided corrosion resistant steel wire			
Maximum Operating Pressure:			
3000.0 pounds per square inch			
Thread Size:			
1.062 inches 2nd end			
Seat Angle:			
37.0 degrees 2nd end			
Hydrostatic Test Pressure:			
6000.0 pounds per square inch			
Flow Angle:			
90.0 degrees 2nd end			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
21.000 inches			

NSN 4720-01-288-1942

Nonmetallic Hose Assembly - Page 2 of 2



Throad	Sorios	Designator	
ımread	i Series	Designator	

Unj 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0