

View Online at <https://aerobasegroup.com/nsn/4720-01-289-8215>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.1875 inches

**Temperature Rating:**

212.0 degrees fahrenheit single response

**Outside Diameter:**

0.484 inches

**Minimum Inside Bending Radius:**

0.750 inches

**End Application:**

2350-00-808-7100 tractor, full tracked

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

6000.0 pounds per square inch

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

0.4375 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Criticality Code Justification:**

Feat

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

12.000 inches working

**Special Features:**

With 3-band markers p/n ms43436/1-3, stamped 1=qdisc 2-3, 2=19207assy12357280-8 mfr (code ident no.) , 3=xmsn p; weapon system essential

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0