NSN 4720-01-290-2512



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-290-2512 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.875 inches **Minimum Inside Bending Radius:** 2.000 inches **End Application:** 2330-01-275-7475 **Connection Style:** Plain 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external pipe 1st end **Burst Test Pressure:** 900.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 225.0 pounds per square inch **Thread Size:** 0.375 inches 1st end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 27.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Nptf 1st end Shelf Life: N/a

Demilitarization:

Unit Of Measure:

No

NSN 4720-01-290-2512

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0