## NSN 4720-01-290-6734

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-290-6734

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response
Outside Diameter:
1.560 inches
Minimum Inside Bending Radius:
6.250 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability and reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
3600.0 pounds per square inch
Layer Composition And Location:
1st layer polytetrafluoroethylene impregnated glass fiber and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
1800.0 pounds per square inch
Inside Surface Condition:
Convoluted
Measuring Method And Length:
253.000 inches
Thread Series Designator

Un 1st end

## NSN 4720-01-290-6734

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	.1+		ife:
J	116		_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0