Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-292-6540

Cross Sectional	I Shape:
Round	
Thread Class:	
2b 1st end	
Thread Direction	n:
Right-hand 1st e	nd
Inside Diameter	:
0.380 inches	
Tempurature Ra	ating:
-40.0 degrees fal	hrenheit single response and 250.0 degrees fahrenheit single response
Outside Diamete	er:
Between 0.750 ir	nches and 0.930 inches
Minimum Inside	e Bending Radius:
5.000 inches	
End Application	1:
2350-00-808-710	00 tractor, full tracked
Connection Styl	le:
Swivel nut, gask	tet seal 1st end
End Connection	ו Design:
Straight 2nd end	
Connection Typ	ie:
Threaded interna	al hose 1st end
Burst Test Pres	sure:
22000.0 pounds	per square inch
Maximum Opera	ating Pressure:
5500.0 pounds p	er square inch
Thread Size:	
0.750 inches 1st	end
Inside Surface C	Condition:
Smooth	
Measuring Meth	nod And Length:
31.500 inches	and 32.500 inches
Special Feature	s:
With 3-band, mar	rkers legends as follows, 1-19207-12334771-1, 2-lh/rh apron cyl rear-20, 3-ckt-20 (upper)bhd
Thread Series D	Designator:
Unf 2nd end	
Shelf Life:	
N/a	
Unit Of Measure	<u>}:</u>
Demilitarization	:
No	

NSN 4720-01-292-6540

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

