Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-292-6541

Cro	oss Sectional Shape:
Rou	und
Thr	read Class:
2b	1st end
Thr	read Direction:
Rig	ht-hand 1st end
Ins	ide Diameter:
0.3	80 inches
Ter	npurature Rating:
-40	.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response
Out	tside Diameter:
Bet	ween 0.750 inches and 0.930 inches
Mir	imum Inside Bending Radius:
5.0	00 inches
End	d Application:
235	0-00-808-7100 tractor, full tracked
Со	nnection Style:
Sw	ivel nut, gasket seal 1st end
End	d Connection Design:
Stra	aight 2nd end
Со	nnection Type:
Thr	eaded internal hose 1st end
Bu	rst Test Pressure:
220	00.0 pounds per square inch
Ma	ximum Operating Pressure:
550	00.0 pounds per square inch
Thr	read Size:
0.7	50 inches 1st end
Ins	ide Surface Condition:
Sm	ooth
Me	asuring Method And Length:
31.	500 inches and 32.500 inches
Spe	ecial Features:
Wit	h 3-band, markers m43436/5-1, with markings, 19207-12334771-2, lh/rh apron cyl fwd-19. Ckt-19 (lower)bhd
Thr	read Series Designator:
Unf	2nd end
She	elf Life:
N/a	
Uni	it Of Measure:
Dei	militarization:
No	

NSN 4720-01-292-6541

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

