

View Online at <https://aerobasegroup.com/nsn/4720-01-292-8812>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

Between 2.938 inches and 3.062 inches

**Temperature Rating:**

-32.0 degrees celsius single response and 52.0 degrees celsius single response

**Outside Diameter:**

Between 3.788 inches and 3.812 inches

**Minimum Inside Bending Radius:**

24.000 inches

**Exterior Color:**

Black

**Hose Or Tubing Specification/std Data:**

Mil-h-370, para 3.3.3.2, type 2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**First End Fitting Specification/std Data:**

Ms27025-15 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Second End Fitting Specification/std Data:**

Ms27021-15 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Quick Disconnect Size:**

3.000 inches 2nd end

**Connection Style:**

Cam or lever (external) 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Internal quick disconnect 1st end

**Features Provided:**

Reusable end fittings

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

300.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer rubber impregnated braided fabric err-100

**Hydrostatic Test Pressure:**

100.0 pounds per square inch

**Outer Covering Environmental Protection:**

Fuel resistant and hydraulic solution resistant and oil resistant and ozone resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

384.000 inches

**Second End Swivel Action Capability:**

Not included

**Special Features:**

Inner conveying tube material-rubber, natural

**Special Markings:**

Black stripe

**Supplementary Features:**

325.0 psi crush resistance

**Specification Data:**

81349-mil-h-370 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0

**Mil-std (military Standard):**

Mil-h-370 spec.