Nonmetallic Hose Assembly - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/4720-01-292-9322

Cross Sectional Sh	ape:		
Round			
Inside Diameter:			
Between 0.359 inches and 0.391 inches Dutside Diameter: Between 0.594 inches and 0.656 inches			
		Minimum Inside Be	nding Radius:
		2.250 inches	
Exterior Color:			
Black			
Connection Style:			
Barbed or serrated e	nd 1st end		
Connection Type:			
Unthreaded external	hose 1st end		
Burst Test Pressure	9:		
1250.0 pounds per s	quare inch		
Layer Composition	And Location:		
1st layer braided fab	ric or 1st layer woven fabric		
Maximum Operating	g Pressure:		
300.0 pounds per sq	uare inch		
Outer Covering Env	vironmental Protection:		
Ozone resistant and	mildew resistant and fuel resistant and vibration resistant and oil resistant		
Inside Surface Con	dition:		
Smooth			
Measuring Method	And Length:		
27.750 inches			
Inside Diameter Ho	se Accommodated:		
0.375 inches 1st end			
Special Features:			
C/o hose, rubber, bla	nck, 0.375 id by 27.0 in. Lg iaw mil-h-13444, type 1; and bsp female swivel, 60 degrees pn 5-45-5173-2		
Media For Which De	esigned:		
Water single respons	Se la		
Shelf Life:			
N/a			
Unit Of Measure:			
 Demilitarization:			
No			
Fiig:			
A542a0			