Nonmetallic Hose Assembly - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/4720-01-292-9324

Cross Sectional S	Shape:
Round	
Inside Diameter:	
Between 0.234 inc	hes and 0.266 inches
Outside Diameter	:
Between 0.469 inc	hes and 0.531 inches
Minimum Inside E	Sending Radius:
2.250 inches	
Exterior Color:	
Black	
Connection Style	
Barbed or serrated	end 1st end
Connection Type	
Jnthreaded extern	al hose 1st end
Burst Test Pressu	ire:
1250.0 pounds per	square inch
Layer Compositio	n And Location:
Ist layer braided fa	bric or 1st layer woven fabric
Maximum Operat	ng Pressure:
300.0 pounds per s	square inch
Duter Covering E	nvironmental Protection:
Ozone resistant ar	d mildew resistant and fuel resistant and vibration resistant and oil resistant
nside Surface Co	ndition:
Smooth	
Measuring Metho	d And Length:
22.000 inches	
nside Diameter H	lose Accommodated:
0.250 inches 1st ei	nd
Special Features:	
C/o hose, rubber, t	black, 0.250 id by 21.500 lg iaw mil-h-13444, type 1; and fitting, swivel, 1/4-bsp 60 degrees pn 5-45-5173-1
Media For Which	Designed:
Water single respo	nse
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A542a0	