

View Online at <https://aerobasegroup.com/nsn/4720-01-292-9325>

Cross Sectional Shape:

Round

Inside Diameter:

Between 0.234 inches and 0.266 inches

Outside Diameter:

Between 0.469 inches and 0.531 inches

Minimum Inside Bending Radius:

2.250 inches

Exterior Color:

Black

Angle Between Rigid Elbow Fittings In Deg:

90.0

Connection Style:

Barbed or serrated end 1st end

Connection Type:

Unthreaded external hose 1st end

Burst Test Pressure:

1250.0 pounds per square inch

Layer Composition And Location:

1st layer braided fabric or 1st layer woven fabric

Maximum Operating Pressure:

300.0 pounds per square inch

Outer Covering Environmental Protection:

Ozone resistant and mildew resistant and fuel resistant and vibration resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.125 inches working

Inside Diameter Hose Accommodated:

0.250 inches 1st end

Special Features:

C/o hose, rubber, black, 0.250 id by 13.500 lg iaw mil-h-13444, type 1; and 2-bsp female 90 deg, swivel elbows pn 5-45-4963

Media For Which Designed:

Water single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0