NSN 4720-01-292-9325

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-292-9325 **Cross Sectional Shape:** Round **Inside Diameter:** Between 0.234 inches and 0.266 inches **Outside Diameter:** Between 0.469 inches and 0.531 inches **Minimum Inside Bending Radius:** 2.250 inches **Exterior Color:** Black Angle Between Rigid Elbow Fittings In Deg: 90.0 **Connection Style:** Barbed or serrated end 1st end **Connection Type:** Unthreaded external hose 1st end **Burst Test Pressure:** 1250.0 pounds per square inch **Layer Composition And Location:** 1st layer braided fabric or 1st layer woven fabric **Maximum Operating Pressure:** 300.0 pounds per square inch **Outer Covering Environmental Protection:** Ozone resistant and mildew resistant and fuel resistant and vibration resistant and oil resistant **Inside Surface Condition:** Smooth

Measuring Method And Length:

15.125 inches working

Inside Diameter Hose Accommodated:

0.250 inches 1st end

Special Features:

C/o hose, rubber, black, 0.250 id by 13.500 lg iaw mil-h-13444, type 1; and 2-bsp female 90 deg, swivel elbows pn 5-45-4963

Media For Which Designed:

Water single response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0