Nonmetallic Hose Assembly - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/4720-01-292-9328



Cross Sectional Shape:

Round

Inside Diameter:

Between 0.234 inches and 0.266 inches

Outside Diameter:

Between 0.469 inches and 0.531 inches

Minimum Inside Bending Radius:

2.250 inches

Exterior Color:

Black

Connection Style:

Barbed or serrated end 2nd end

Connection Type:

Unthreaded external hose 2nd end

Burst Test Pressure:

1250.0 pounds per square inch

Layer Composition And Location:

1st layer braided fabric or 1st layer woven fabric

Maximum Operating Pressure:

300.0 pounds per square inch

Outer Covering Environmental Protection:

Ozone resistant and mildew resistant and fuel resistant and vibration resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

16.500 inches excluding end fittings

Inside Diameter Hose Accommodated:

0.250 inches 2nd end

Special Features:

C/o hose, rubber, black, 0.250 id by 16.500 lg iaw mil-h-13444, type 1; and fitting, swivel, 1/4-bsp 60 degrees pn 5-45-5173-1; and 1/4-bsp female 90 degrees swivel, elbow pn 5-45-4963

Media For Which Designed:

Water single response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0