NSN 4720-01-292-9331

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-292-9331

Cross Sectional Shape:
Round
Inside Diameter:
Between 0.234 inches and 0.266 inches
Outside Diameter:
Between 0.469 inches and 0.531 inches
Minimum Inside Bending Radius:
2.250 inches
Exterior Color:
Black
Connection Style:
Barbed or serrated end 2nd end
Connection Type:
Unthreaded external hose 2nd end
Burst Test Pressure:
1250.0 pounds per square inch
Layer Composition And Location:
1st layer braided fabric or 1st layer woven fabric
Maximum Operating Pressure:
300.0 pounds per square inch
Outer Covering Environmental Protection:
Ozone resistant and mildew resistant and fuel resistant and vibration resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
28.250 inches excluding end fittings
Inside Diameter Hose Accommodated:
0.250 inches 2nd end
Special Features:
C/o hose, rubber, black, 0.250 id by 28.250 lg iaw mil-h-13444, type 1; and fitting, swivel, 1/4-bsp 60 degrees pn 5-45-5173-1; and 1/4-bsp
female 90 degrees swivel, elbow pn 5-45-4963
Media For Which Designed:
Water single response
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Filig:
A542a0