

View Online at <https://aerobasegroup.com/nsn/4720-01-294-1081>

Cross Sectional Shape:

Round

Inside Diameter:

1.125 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

1.500 inches

Minimum Inside Bending Radius:

9.000 inches

Exterior Color:

Black

Angle Between Rigid Elbow Fittings In Deg:

100.0

Center To Center Distance Between Bolt Holes Along Width:

1.656 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.656 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.188 inches 2nd end

Flange Width:

2.188 inches 2nd end

Connection Style:

Plain 2nd end

Bolt Hole Diameter:

0.266 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Plain face flange 2nd end

Features Provided:

Reusable end fittings

Burst Test Pressure:

2500.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and 2nd layer braided cotton cord and outer layer braided cotton cord

Maximum Operating Pressure:

600.0 pounds per square inch

Hydrostatic Test Pressure:

1200.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

14.750 inches

Flange Style:

Rectangular (includes square) 2nd end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0