NSN 4720-01-295-7618

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-295-7618

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.391 inches
Tempurature Rating:
-55.0 degrees celsius single response and 204.0 degrees celsius single response
Outside Diameter:
0.585 inches
Minimum Inside Bending Radius:
1.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability and reusable end fittings
Burst Test Pressure:
6000.0 pounds per square inch
6000.0 pounds per square inch Layer Composition And Location:
Layer Composition And Location:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.750 inches 1st end
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 9.000 inches
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 9.000 inches Thread Series Designator:
Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Convoluted Measuring Method And Length: 9.000 inches Thread Series Designator: Unf 1st end

--

NSN 4720-01-295-7618

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0