NSN 4720-01-296-0411

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-296-0411

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response
Outside Diameter:
0.469 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1250.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and outer layer molded rubber, synthetic
Maximum Operating Pressure:
200.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
400.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
180.000 inches working
Media For Which Designed:
Air single response
Thread Series Designator:
Unf 1st end
Specification Data:
88044-an6270 government standard

NSN 4720-01-296-0411

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0