

View Online at <https://aerobasegroup.com/nsn/4720-01-296-2351>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.562 inches

Temperature Rating:

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

1.031 inches

Minimum Inside Bending Radius:

6.500 inches

Angle Between Rigid Elbow Fittings In Deg:

270.0

End Application:

2320-01-123-1608, light armored vehical

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.875 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

42.000 inches working

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms28924 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0