NSN 4720-01-296-2353

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-296-2353

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.344 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.547 inches
Minimum Inside Bending Radius:
2.500 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
2500.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
15.750 inches
Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-01-296-2353

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unjf 1st end
Specification Data:
81349-ms83796/1 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A542a0