

View Online at <https://aerobasegroup.com/nsn/4720-01-296-6885>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.235 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 1000.0 degrees fahrenheit single response

**Outside Diameter:**

0.439 inches

**Minimum Inside Bending Radius:**

6.250 inches

**Inner Conveying Tube Style:**

Annular close-pitch corrugated

**Angle Between Rigid Elbow Fittings In Deg:**

325.0

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Elbow 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

480.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

120.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

240.0 pounds per square inch

**Flow Angle:**

45.0 degrees 2nd end

**Measuring Method And Length:**

19.000 inches

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A542a0