## NSN 4720-01-296-6885

Metallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-296-6885
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.235 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 1000.0 degrees fahrenheit single response
Outside Diameter:
0.439 inches
Minimum Inside Bending Radius:
6.250 inches
Inner Conveying Tube Style:
Annular close-pitch corrugated
Angle Between Rigid Elbow Fittings In Deg:
325.0
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Elbow 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
480.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
120.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end

**Hydrostatic Test Pressure:** 

240.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

**Measuring Method And Length:** 

19.000 inches

**Thread Series Designator:** 

Unf 2nd end

## NSN 4720-01-296-6885

Metallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0