## NSN 4720-01-296-6890

14.750 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-296-6890

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.438 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 375.0 degrees fahrenheit single response
Outside Diameter:
0.641 inches
Minimum Inside Bending Radius:
3.500 inches
Angle Between Rigid Elbow Fittings In Deg:
90.0
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
2500.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:

## NSN 4720-01-296-6890

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0

Mil-std (military Standard):

Mil-h-83796 spec.