## NSN 4720-01-296-9298



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-296-9298 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.513 inches **Minimum Inside Bending Radius:** 1.250 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 10000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided synthetic cord and outer layer molded polyurethane **Maximum Operating Pressure:** 2750.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Outer Covering Environmental Protection:** Oil resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 12.000 inches working **Thread Series Designator:** 

Unf 1st end Shelf Life:

N/a

## NSN 4720-01-296-9298

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0