Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-296-9311

New Online at https://aerobasegroup.com/nsi/4/20-01-230-3511
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.700 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
1st layer braided polyamide cord and 2nd layer braided polyester cord and outer layer molded polyurethane
Maximum Operating Pressure:
2250.0 pounds per square inch
Thread Size:
0.563 inches 1st end
Seat Angle:
37.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
28.000 inches working
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 4720-01-296-9311

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

