

View Online at <https://aerobasegroup.com/nsn/4720-01-297-5130>

Cross Sectional Shape:

Round

Thread Class:

3b 2nd end

Thread Direction:

Right-hand 2nd end

Inside Diameter:

1.125 inches

Temperature Rating:

-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

1.437 inches

Minimum Inside Bending Radius:

8.000 inches

Angle Between Rigid Elbow Fittings In Deg:

210.0

Center To Center Distance Between Bolt Holes Along Width:

0.266 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

0.266 inches 1st end

Bolt Hole Quantity:

4 1st end

Flange Length:

2.188 inches 1st end

Flange Width:

2.188 inches 1st end

Connection Style:

Swivel nut flare 2nd end

Bolt Hole Diameter:

0.266 inches 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Elbow 2nd end

Connection Type:

Threaded internal tube 2nd end

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

500.0 pounds per square inch

Thread Size:

1.625 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

1300.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

18.375 inches

Flange Style:

Rectangular (includes square) 1st end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0