Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-297-6468

Cross S	Sectional Shape:
Round	
Thread	Class:
3b 1st e	nd
Thread	Direction:
Right-ha	and 1st end
Inside D	Diameter:
0.438 in	ches
Tempur	rature Rating:
-65.0 de	grees fahrenheit and 250.0 degrees fahrenheit single response
Outside	Diameter:
0.641 in	ches
Minimu	m Inside Bending Radius:
3.500 in	ches
Connec	tion Style:
Swivel n	nut flare 2nd end
End Co	nnection Design:
Straight	1st end
Connec	tion Type:
Threade	ed internal tube 1st end
Feature	s Provided:
Reusabl	le end fittings
Burst T	est Pressure:
2500.0 p	bounds per square inch
Layer C	composition And Location:
1st layei	r braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Maximu	Im Operating Pressure:
1000.0 p	bounds per square inch
Thread	Size:
0.750 in	ches 2nd end
Seat An	igle:
37.0 deç	grees 2nd end
Hydrost	tatic Test Pressure:
5000.0 p	pounds per square inch
Flow Ar	ngle:
45.0 deç	grees 2nd end
Inside S	Surface Condition:
Smooth	
Measur	ing Method And Length:
6.000 in	ches
Media F	For Which Designed:
Fuel/oil.	hydrocarbon single response

NSN 4720-01-297-6468

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unjf 1st end

Specification Data:

81349-mil-h-83796/1 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A542a0