## NSN 4720-01-297-6482

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-297-6482

One of Octional Observe
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.125 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 375.0 degrees fahrenheit single response
Outside Diameter:
1.437 inches
Minimum Inside Bending Radius:
8.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
2000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
500.0 pounds per square inch
Thread Size:
1.625 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
1300.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
53.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:

Unjf 1st end

## NSN 4720-01-297-6482

Nonmetallic Hose Assembly - Page 2 of 2



Shelf	Life:
•	

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-83796 spec.