Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-297-8060

Cross	Sectional	Shape:

Round

Thread Class:

3b 1st end

# Thread Direction:

Right-hand 1st end

# Inside Diameter:

0.188 inches

### **Tempurature Rating:**

-55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

### **Outside Diameter:**

0.484 inches

Minimum Inside Bending Radius:

2.000 inches

### **Exterior Color:**

Natural

### **Connection Style:**

Swivel nut flare 1st end

### **End Connection Design:**

Straight 1st end

# Connection Type:

Threaded internal tube 1st end

## **Features Provided:**

Reusable end fittings

### **Burst Test Pressure:**

6000.0 pounds per square inch

### Layer Composition And Location:

1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabric

### Maximum Operating Pressure:

1500.0 pounds per square inch

#### Thread Size:

0.438 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

### Hydrostatic Test Pressure:

3000.0 pounds per square inch

# **Outer Covering Environmental Protection:**

Fuel resistant and mildew resistant and oil resistant

## Vacuum In Torr:

50.0

# Inside Surface Condition:

Smooth



Measuring Method And Length:

196.000 inches working

# Media For Which Designed:

Fuel/oil, hydrocarbon single response

# Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0