NSN 4720-01-298-3249

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-298-3249

Cross Sectional Shape:
Round
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.090 inches
Minimum Inside Bending Radius:
5.500 inches
Quick Disconnect Size:
0.750 inches 1st end
Connection Style:
Cam or lever (internal) 1st end
End Connection Design:
Straight 1st end
Connection Type:
Internal quick disconnect 1st end
Burst Test Pressure:
500.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Operating Pressure:
125.0 pounds per square inch
Hydrostatic Test Pressure:
250.0 pounds per square inch
Vacuum In Torr:
508.0
Inside Surface Condition:
Smooth
Measuring Method And Length:
240.000 inches excluding end fittings
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A542a0