## NSN 4720-01-299-0441

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-299-0441

**Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.188 inches **Tempurature Rating:** -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response **Outside Diameter:** 0.343 inches **Minimum Inside Bending Radius:** 2.000 inches **Exterior Color:** Blue Angle Between Rigid Elbow Fittings In Deg: 180.0 **Connection Style:** Swivel nut, inverted flare 2nd end **End Connection Design:** Elbow 2nd end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 8.5 degrees 2nd end **Hydrostatic Test Pressure:** 6000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end

50.8

**Vacuum In Torr:** 

## NSN 4720-01-299-0441

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
22.900 inches
Supplementary Features:
This item has been reviewed for asbestos material; the current approved sources, 00624 have indicated their part number contained
asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984
Thread Series Designator:
Unjs 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0