NSN 4720-01-299-4048

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-299-4048 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -67.0 degrees fahrenheit and 160.0 degrees fahrenheit single response **Outside Diameter:** 0.765 inches **Minimum Inside Bending Radius:** 1.250 inches **Connection Style:** Swivel nut, gasket seal 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal hose 1st end **Features Provided:** Electrostatic discharge capability Thready Qty Per Inch (tpi): 16 1st end **Burst Test Pressure:** 1000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided synthetic cord and outer layer braided polyester cord **Maximum Operating Pressure:** 150.0 pounds per square inch **Thread Size:** 0.688 inches 1st end **Hydrostatic Test Pressure:** 300.0 pounds per square inch **Outer Covering Environmental Protection:** Fire retardant **Inside Surface Condition:** Convoluted **Measuring Method And Length:**

Media For Which Designed:

Water single response

22.750 inches and 23.250 inches

NSN 4720-01-299-4048

Nonmetallic Hose Assembly - Page 2 of 2



Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0