Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-299-4049

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-67.0 degrees fahrenheit and 160.0 degrees fahrenheit single response
Outside Diameter:
0.765 inches
Minimum Inside Bending Radius:
1.250 inches
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal hose 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
16 1st end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided synthetic cord and outer layer braided polyester cord
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
0.688 inches 1st end
Hydrostatic Test Pressure:
300.0 pounds per square inch
Outer Covering Environmental Protection:
Fire retardant
Inside Surface Condition:
Convoluted
Measuring Method And Length:
20.250 inches and 20.750 inches
Media For Which Designed:
Water single response

Nonmetallic Hose Assembly - Page 2 of 2



**Thread Series Designator:** 

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0