NSN 4720-01-300-2990

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-300-2990

0.297 inches
Tempurature Rating:
-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
2.500 inches
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
12.0 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
18.125 inches

NSN 4720-01-300-2990

Nonmetallic Hose Assembly - Page 2 of 2



Special Features:
Hose assembly wt: 0.58 lb max
Media For Which Designed:
Fuel/oil, hydrocarbon single response and water single response
Thread Series Designator:
Unjf 1st end
Specification Data:
81349-mil-h-38360, size 6 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0