Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-301-0356

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.250 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Outside Diameter:	
0.500 inches	
Minimum Inside Bending Radius:	
2.000 inches	
Exterior Color:	
Black	
Connection Style:	
Plain 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded external pipe 1st end	
Burst Test Pressure:	
20000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided wire and 2nd layer braided wire and outer layer molded rubber, synthetic	
Maximum Operating Pressure:	
5000.0 pounds per square inch	
Thread Size:	
0.250 inches 1st end	
Hydrostatic Test Pressure:	
10000.0 pounds per square inch	
Outer Covering Environmental Protection:	
Abrasion resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
30.000 inches	
Special Features:	
Special cleaning for oxygen service iaw mil-c-52211	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Nptf 1st end	

NSN 4720-01-301-0356

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

