Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-303-2455

**Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 1.500 inches Hose Or Tubing Specification/std Data: Zz-h-561, type 2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Connection Style:** Swivel nut, gasket seal 1st end **End Connection Design:** Straight 1st end **End Fitting Component And Material:** Complete fitting steel all ends **Connection Type:** Threaded internal pipe 1st end Second End Relationship With First End: Identical **Burst Test Pressure:** 100.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer molded rubber, synthetic err-100 Maximum Operating Pressure: 50.0 pounds per square inch **Thread Size:** 0.250 inches 1st end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 120.000 inches **Special Features:** Inner conveying tube material-rubber, synthetic Media For Which Designed: Water, drinking single response **Thread Series Designator:** Npt 1st end **Specification Data:** 81348-zz-h-561 government specification **Specification Or Standard:** 

B grade and 2 class and 1.500 size

## NSN 4720-01-303-2455

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

