## NSN 4720-01-303-6387

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-303-6387

view Offilite at https://aerobasegroup.com/hsr//4/20-01-300-000/	
Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.750 inches	
Tempurature Rating:	
-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response	
Outside Diameter:	
1.188 inches	
Minimum Inside Bending Radius:	
3.500 inches	
Angle Between Rigid Elbow Fittings In Deg:	
145.0	
Connection Style:	
Swivel nut flare 2nd end	
End Connection Design:	
Elbow 2nd end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Electrostatic discharge capability and reusable end fittings	
Thready Qty Per Inch (tpi):	
12 2nd end	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
1.062 inches 2nd end	
Seat Angle:	

37.0 degrees 2nd end

### **Hydrostatic Test Pressure:**

6000.0 pounds per square inch

### Flow Angle:

90.0 degrees 2nd end

### **Outer Covering Environmental Protection:**

Heat resistant and fuel resistant and oil resistant and solvent resistant and vibration resistant

# NSN 4720-01-303-6387

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
<b>Measuring Method And Length:</b>
22.250 inches
Thread Series Designator:
Unj 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0