Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-304-3895

Cross Sectional Shape: Round Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.219 inches Tempurature Rating: of.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: 0.440 inches Minimum Inside Bending Radius: 2.000 inches Swivel nut with compression sleeve 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 6000.0 pounds per square inch
Tread Class:3b 1st endThread Direction:Right-hand 1st endInside Diameter:0.219 inchesTempurature Rating:-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single responseOutside Diameter:0.440 inchesSuite Diameter:2.000 inchesConnection Style:Swivel nut with compression sleeve 2nd endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endBurst Test Pressure:
3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.219 inches Tempurature Rating: -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: 0.440 inches Minimum Inside Bending Radius: 2.000 inches Connection Style: Swivel nut with compression sleeve 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Thread Direction:Right-hand 1st endInside Diameter:0.219 inchesTempurature Rating:-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single responseOutside Diameter:0.440 inchesMinimun Inside Bending Radius:2.000 inchesConnection Style:Swivel nut with compression sleeve 2nd endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endBurst Test Pressure:
Right-hand 1st endInside Diameter:0.219 inchesTempurature Rating:-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single responseOutside Diameter:0.440 inchesMinimun Inside Bending Radius:2.000 inchesConnection Style:Swivel nut with compression sleeve 2nd endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endBurst Test Pressure:
Inside Diameter: 0.219 inches Tempurature Rating: -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: 0.440 inches 0.440 inches Minimum Inside Bending Radius: 2.000 inches 2.000 inches 2.000 inches Connection Style: Swivel nut with compression sleeve 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
0.219 inches Tempurature Rating: -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: 0.440 inches 0.440 inches Minimum Inside Bending Radius: 2.000 inches 2.000 inches Connection Style: Swivel nut with compression sleeve 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Bust Test Pressure:
Tempurature Rating: -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: 0.440 inches Minimun Inside Bending Radius: 2.000 inches 2.000 inches Connection Style: Swivel nut with compression sleeve 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response Outside Diameter: 0.440 inches Minimum Inside Bending Radius: 2.000 inches Connection Style: Swivel nut with compression sleeve 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Outside Diameter: 0.440 inches Minimum Inside Bending Radius: 2.000 inches Connection Style: Swivel nut with compression sleeve 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
D.440 inches Minimum Inside Bending Radius: 2.000 inches Connection Style: Swivel nut with compression sleeve 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Minimum Inside Bending Radius: 2.000 inches Connection Style: Swivel nut with compression sleeve 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
2.000 inches Connection Style: Swivel nut with compression sleeve 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Connection Style: Swivel nut with compression sleeve 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Swivel nut with compression sleeve 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Connection Type: Threaded internal tube 1st end Burst Test Pressure:
Threaded internal tube 1st end Burst Test Pressure:
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
1st layer rubber impregnated braided corrosion resistant steel wire and outer layer spirally laid corrosion resistant steel wi
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
42.500 inches
Special Test Features:
Hose cert to faa tso-c53a typea
Thread Series Designator:
Unjf 1st end

NSN 4720-01-304-3895

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

